PRODUCT INFORMATION

Description 12-24V LED White Zone Light

 Height
 123.70 mm / 4.87 in

 Width
 258.57 mm / 10.18 in

 Depth
 102.11 mm / 4.02 in

Shape Rectangular

Outer Lens MaterialGlassOuter Lens ColorClearHousing MaterialXenoyHousing ColorBlack

Mounting Hardware Description(x2) M8-1.25 Mounting BoltMounting TypeUniversal Pedestal Mount

Minimum Operating -40 °C / -40 °F

Temperature

Maximum Operating 65 °C / 149 °F

Temperature

Connector or Wiring Integrated 2-Pin Deutsch Weatherproof

Socket (DT04-2P)


Mating Connector Integrated 2-Pin Deutsch Weatherproof

Plug (DT06-2S)

Product Weight 2.60 lbs / 1.18 kgs **Shipping Weight** 5.60 lbs / 2.54 kgs



PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage 12-24V AC **Operating Voltage** 10-32V AC

Transient Spike Protection 150V Peak @ 1 HZ-100 Pulses

Red WirePositiveBlack WireNegative

Current Draw 1.2A @ 12V AC .8A @ 24V AC


REGULATORY STANDARDS COMPLIANCE







Buy America Standards IEC IP69K Eco Friendly





PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 1,500 **Effective Lumen**

Output

640

Beam Pattern(s)

Forward Lighting - Spot Warning - Keep Out Zone

APPLICATIONS



















PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

ACCESSORIES



Part Number 8200151 Rock Guard Kit for Model 527

Print date: 2020-12-03

RELATED PRODUCTS



Part Number 0549271 12-24V LED Red Zone Light



Part Number 0551271 12-24V LED Green Zone Light



Part Number 0551281 12-24V LED Amber Zone Light



Part Number 0647011 12-24V LED Red & Green Signal Light



Part Number 0647021 12-24V LED Amber & Green Signal Light